

SAFETY DATA SHEET

1. Identification

Product identifier	Oneshot Cartridges Ink, color	: black
Other means of identification	None.	
Recommended use	Marking.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Company name	BERASIT GmbH + Co. KG	
Address	Lademannbogern 65m, 22339 H	lamburg +49
Telephone	40 538096611	
Fax	+49 40 538096656	
E-Mail	info@berasit.de	
Emergency phone number	Emergency telephone	See Manufacturer/Supplier (during the office hours)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
OSHA defined hazards	Not classified.	
Label elements		
	$\wedge \wedge$	

 \times

	· ·
Signal word	Warning
Hazard statement	Flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Diacetone alcohol	123-42-2	60-80
Carbon black	1333-86-4	2.5-10

Dipropylene glycol butyl ether	29911-28-2	2.5-10
Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Gas con percent by volume.	centrations are in
4. First-aid measures		
nhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISO CENTER or doctor/physician if you feel unwell.	
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove corpresent and easy to do. Continue rinsing. Get medical attention if irritation deve	
ngestion	Rinse mouth thoroughly. If ingestion of a large amount does occur, call a poise immediately.	on control center
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swellir vision. May cause respiratory irritation.	ng, and blurred
ndication of immediate nedical attention and special reatment needed	Provide general supportive measures and treat symptomatically. Keep victim u Symptoms may be delayed.	Inder observation
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical label where possible). Ensure that medical personnel are aware of the materia take precautions to protect themselves. Wash contaminated clothing before re	I(s) involved, and
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Jnsuitable extinguishing nedia	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from he chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable of ignition and flash back. During fire, gases hazardous to health may be formed	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in	a case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fir so without risk.	e area if you can
Specific methods	Use standard firefighting procedures and consider the hazards of other involve	d materials.
General fire hazards	Flammable liquid and vapor.	
6. Accidental release meas	ures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spi ignition sources (no smoking, flares, sparks, or flames in immediate area). We protective equipment and clothing during clean-up. Avoid breathing mist or van damaged containers or spilled material unless wearing appropriate protective of closed spaces before entering them. Local authorities should be advised if sign cannot be contained. For personal protection, see section 8 of the SDS.	ar appropriate oor. Do not touch clothing. Ventilate
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immedia precautionary measures against static discharge. Use only non-sparking tools. (wood, paper, oil, etc.) away from spilled material.	
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to divert vapor cloud drift. Dike the spilled material, where this is possible. Cover prevent spreading. Use a non-combustible material like vermiculite, sand or ear product and place into a container for later disposal. Clean up in accordance we regulations. Following product recovery, flush area with water.	with plastic sheet arth to soak up the
	Small Spills: Absorb with earth, sand or other non-combustible material and tra for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean so remove residual contamination.	
	Never return spills to original containers for re-use. For waste disposal, see se	ction 13 of the SE
	Never return spills in original containers for re-use. For waste disposal, see Se	ction 13 of the SI
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	

7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid breathing mist or vapor. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store between 35°F (2°C) and 120°F (49°C).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Diacetone alcohol (CAS 123-42-2)	PEL	240 mg/m3	
- /		50 ppm	
US. ACGIH Threshold Lim	it Values		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3 I	nhalable fraction.
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Diacetone alcohol (CAS 123-42-2)	TWA	240 mg/m3	
		50 ppm	
ological limit values	No biological exposure limits noted fo	r the ingredient(s).	
propriate engineering ntrols	Explosion-proof general and local exh changes per hour) should be used. Ve applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels	entilation rates should be matched to ocal exhaust ventilation, or other eng mended exposure limits. If exposure	o conditions. If gineering controls to e limits have not beer
dividual protection measure	s, such as personal protective equipme	ent	
Eye/face protection	Wear approved safety goggles.		
Skin protection			
Hand protection	Wear appropriate chemical resistant g	gloves.	
Other	Wear suitable protective clothing.		
Respiratory protection	When workers are facing concentratic certified respirators.	ons above the exposure limit they m	ust use appropriate
Thermal hazards	Wear appropriate thermal protective of	lothing, when necessary.	
eneral hygiene nsiderations	When using do not smoke. Always ob after handling the material and before clothing and protective equipment to r	eating, drinking, and/or smoking. R	
Physical and chemica	l properties		
	Black liquid		

9.

Appearance	Black liquid.	
Physical state	Liquid.	
Form	Liquid.	
GS-1 Black		SDS US

Color	Black.
Odor	Characteristic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	302 °F (150 °C)
Flash point	132.8 °F (56.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	

Explosive limit - lower (%)	1.4 % v/v
Explosive limit - upper (%)	8.1 % v/v
Vapor pressure	1.1 hPa /1 mmHg (25°C/68°F)
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Moderately soluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	1148 °F (620 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.00 g/cm³ (20°C/68°F)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong bases. Alkali metals. Halogens.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	May cause mild skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity	May cause respiratory irritation. May cause discomfort if swallowed.
Skin corrosion/irritation	Prolonged or repeated contact may dry skin and cause dermatitis.
Serious eye damage/eye	Causes serious eye irritation.
irritation	

Desnireten, er skin sensitizetier		
Respiratory or skin sensitizatior Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are	
Germ cen mutagementy	mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Inhalation of carbon black dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	
Carbon black (CAS 1333-		
OSHA Specifically Regulate Not listed.	d Substances (29 CFR 1910.1001-1050)	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause respiratory irritation.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	No data available.	
Chronic effects	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. The product contains organic solvents which may be absorbed into the body by skin contact and cause permanent damage to the nervous system, including the brain.	
12. Ecological information		
Ecotoxicity	The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data available.	
Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating.	
Partition coefficient n-octanol / water (log Kow) Diacetone alcohol (CAS 123-42-2) -0.098		
Mobility in soil	This product is moderately water soluble and may disperse in soil.	
Other adverse effects	None known.	
13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	D001: Waste Flammable material with a flash point <140 °F	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of waste and residues in accordance with local authority requirements.	

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1210
UN proper shipping name	Printing ink, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, IB3, T2, TP1
Packaging exceptions	150

Packaging non bulk	173	
Packaging bulk	242	
UN number UN proper shipping name	UN1210 Printing ink flammable	
Transport hazard class(es)		
Class	3	
Subsidiary risk	-	
Label(s)	3	
Packing group	III	
Environmental hazards	No	
ERG Code	3L	
	Read safety instructions, SDS and emergency procedures before handling.	
IMDG		
UN number UN proper shipping name	UN1210 PRINTING INK FLAMMABLE	
Transport hazard class(es)		
Class	3	
Subsidiary risk	- ·	
Label(s)	3	
Packing group	III	
Environmental hazards		
Marine pollutant	No	
EmS	F-E, S-D	
Transport in bulk according to	Read safety instructions, SDS and emergency procedures before handling. Not established.	
Annex II of MARPOL 73/78 and		
the IBC Code		
15 Pagulatory information		
15. Regulatory information		
US federal regulations	This product is hazardous according to OSHA 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.	
	CERCLA/SARA Hazardous Substances - Not applicable.	
TSCA Section 12(b) Export N	lotification (40 CFR 707, Subpt. D)	
Not regulated.		
	l Substances (29 CFR 1910.1001-1050)	
Not listed. CERCLA Hazardous Substar	000 List (40 CEP 302 4)	
Not listed.		
	sutherization Act of 1096 (CADA)	
Superfund Amendments and Rea Hazard categories	Immediate Hazard - Yes	
nazaru categories	Delayed Hazard - No	
	Fire Hazard - Yes	
	Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazard	-	
Not listed.		
SARA 311/312 Hazardous	Yes	
chemical	165	
SARA 313 (TRI reporting)		
Not regulated.		
·		
Other federal regulations		
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List		
Not regulated.	119(a) Appletental Deleges Descentions (10 OED 00 100)	
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated.		
inot regulated.		

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2)

US. New Jersey Worker and Community Right-to-Know Act

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65 Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
*A "Ves" indicates this produc	t complies with the inventory requirements administered by the governing country(s)	

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	13-April-2015
Revision date	-
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS® ratings	Health: 2 Flammability: 2 Physical hazard: 0
NFPA ratings	

Disclaimer

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.