




Technical Data Sheet



UniPak 195 x 195 mm 1500 ml

Logical no: 5541
Available lids: 2540 standard

Volume

Volume under lid: 1500,0 ml +/- ml **Volume brimful:** 1870,0 ml +/- ml

Dimensions

Shape:	Square	Length bottom:	177 mm +/- 0,5 mm
Length top with std. lid:	195,9 mm +/- 0,5 mm	Width bottom:	177 mm +/- 0,5 mm
Length top without std. lid:	195,9 mm +/- 0,5 mm	Height without lid:	61 mm +/- 0,5 mm
Width top without std. lid:	195,9 mm +/- 0,5 mm	Height with std lid:	61,5 mm +/- 0,5 mm
Width top with std. lid:	195,9 mm +/- 0,5 mm		

Weight

Weight container/pot: 56 g +/- g
Weight standard lid: 30 g +/- 3 g

Performance

Stackability - dynamic: Max: kg Max top load on bottom container **UN approval:** No
 at 23°

Stacking tests: **Special:**
 The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

Closure system

Lid type options: Standard lid
Closure type: Snap-On
Protective collar: Yes
Tamper Evidence type: Tamper Evidence tab

Handle

Handle available: None

Decoration

Decoration available: IML **Decoration area offset:** NA mm without overlap

Packing

On pallet 1200x800:	2592 pcs.	On pallet 800x1200:	2880 pcs.
Pieces per layer:	NA pcs.	Pieces per layer:	NA pcs.
Height incl. pallet:	1,91 m	Height incl. pallet:	2,18 m
Stackability, empty:	1 pallets high	Stackability, empty:	1 pallets high

Raw material

Raw material options: PP **Masterbatch colours:** Colours according to RPC Superfos standard selected pantone colours.
Hot filling: 85-95° C

Hot temperatures:
 The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures

Cold temperatures:
 Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures

Quality Specifications

Approvals: All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very

Quality information:

low temperatures or very high temperatures over a long period.
Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Specifications are subject to change without notice. Version 10.2

Latest revision : 06-03-2014