



Slim LED



Minimalistic design and shape are characteristic points of Slim LED luminaire. Binned LED of renowned producers of high efficacy, long life time and high reliability makes Slim LED a perfect lighting solution for representative office and hotel spaces. The luminaire has a very low glare rating. Smooth, adjustable suspension brackets make installation an easy task.

Materials: Housing made of aluminum profile, painted electrostatically (standard color: grey).

Installation: Suspended (suspension included).

Power: 230V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Light source power	27W
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes
Luminaire power	27 W
Type of LED	5630
Power factor	0.98

MECHANICAL DATA

Type of installation	Suspended
Housing material	Aluminum
Electrical track connection	No

CERTIFICATES

Degree of protection (IP)	IP40
Class of protection	I
Energy class	A+
CE	Yes
For ceiling installation, fire class "F" (L)	Yes

LIGHT DATA

Light colour	White
Color rendering index	80
Light distribution	Mid beam
Light distribution	DI
Class of luminaire	I


OPTICAL DATA

Louver/shutter	PAR
Diffuser colour	None
Diffuser material	Prismatic plastic
Louver material	Aluminum
Reflector	High gloss

AVAILABLE VARIANTS

Product code	Light source power [W]	Luminaire luminous flux [lm]	Luminaire luminous efficacy [lm/W]	Colour temperature [K]	Colour	Info	Weight [kg]
PX4059130	1×27	2910	108	3000	White	-	2.0
PX4059140	1×27	2970	110	4000	White	-	2.0
PX4059150	1×27	2910	108	3000	Grey	-	2.0
PX4059160	1×27	2970	110	4000	Grey	-	2.0
PX4059135	1×27	2910	108	3000	White	GK	2.7
PX4059145	1×27	2970	110	4000	White	GK	2.7
PX4059155	1×27	2910	108	3000	Grey	GK	2.7
PX4059165	1×27	2970	110	4000	Grey	GK	2.7

DIMENSIONS



L [mm]	W [mm]	H [mm]
1109	48	26

L = Length | W = Width | H = Height / Depth

