






Betonskrue Indu-Prog, TX-kær

Artikel: 105 267 BETONGSKRUV INDU-P 7,5X65-100
 BETONGSKRUV INDU-PROG 7,5X65 TX30 BLANKFÖRZINKAD



Betonskrue IP.mål



ESSBOX

Art.nr.	Dimension dk x L mm	D mm	Bor Ø mm	Bore- dybde* mm	Maks. emne- tykkelse* mm	Bits nr.	ESSBOX- størrelse	Antal/ enhed	Enheder/ storpak
105 267	7,5 x 65	10	6	45/60	30/15	TX30	204	100	6
105 287	7,5 x 92	10	6	45/60	67/42	TX30	204	50	6
105 288	7,5 x 132	10	6	45/60	107/82	TX30	204	50	6

*Ved anbefalet forankringsdybde i beton

Småpak

Art.nr.	Dimension dk x L mm	D mm	Bore- dybde* mm	Maks. emne- tykkelse* mm	Bits nr.	Antal/ enhed
511 280	7,5 x 65	10	45/60	30/15	TX30	6
511 296	7,5 x 92	10	45/60	67/42	TX30	8
511 297	7,5 x 132	10	45/60	107/82	TX30	8

Bulkenheder

Art.nr.	Dimension dk x L mm	D mm	Bor Ø mm	Bore- dybde* mm	Maks. emne- tykkelse* mm	Bits nr.	Antal/ enhed
710 52 87	7,5 x 92	10	6	45/60	67/42	TX30	1100
710 52 88	7,5 x 132	10	6	45/60	107/82	TX30	900

*Ved anbefalet forankringsdybde i beton

Anbefalet forankringsdybde*

Materiale	Ø 7,5	Ø 6,3
Beton	35/50 mm	25 mm
Mursten	50 mm	40 mm
Hulblokke	60 mm	50 mm

*Boreddybde = forankringsdybde + min. 10 mm

Praktisk belastningsevne

Dimension mm	Monteringsdybde mm	Træklast kN Beton C20/25	Træklast kN Huldæk- element C60/75*	Tværbelastning kN Beton C20/25	Tværbelastning kN Huldæk- element C60/75*	Min. kant- afstand Træklast mm	Min. kant- afstand Tværbelastning mm	Min. indbyrdes afstand mm	Tilspændings- moment Nm
6,3	25	0,8		1,4		40	50	100	10
7,5	35	1,0	1,1	2,6	3,4	60	80	140	10
7,5	50	2,4		2,6		60	80	140	10
10,5	45	4,0		3,5		80	90	160	**
10,5	60	5,3		3,5		100	90	200	**
12,5	50	4,5		4,3		100	120	200	**
12,5	70	7,5		4,3		120	120	240	**

Brandklasse

Dimension 7,5 mm er godkendt i brandklasse R30 for en belastning på 1,0 kN. Min. monteringsdybde: 35 mm.