



Appliance Oven Tubular



App 40.0W E14 230-240V T29 OV ICT

Tubular vacuum lamps with clear glass (T-bulb)

Product data

| General Information | | |
|-------------------------------------|----------------------------|--|
| Cap base | EI4 [EI4] | |
| Operating position | UNIVERSAL [Any/Universal] | |
| Main application | Oven | |
| Nominal lifetime (nom.) | 1000 h | |
| Switching cycle | 4,000X | |
| Rated lifetime (hours) | 1000 h | |
| | Sphere | |
| Light Technical | | |
| Luminous flux (nom.) | 300 lm | |
| Luminous flux (rated) (nom.) | 300 lm | |
| Chromaticity coordinate X (nom.) | 0.460 | |
| Chromaticity coordinate Y (nom.) | 0.411 | |
| Correlated Colour Temperature (Nom) | 2600K | |
| Colour rendering index (nom.) | 100 | |
| Operating and Electrical | | |
| · • | | |
| Power (Rated) (Nom) | 40.0 W | |
| Lamp current (nom.) | 0.17 A | |
| Starting time (nom.) | 0.0 s | |
| Warm-up time to 60% light (nom.) | instant full light | |
| Power factor (nom.) | 1 | |
| | | |

| Voltage (Nom) | 230-240 V |
|------------------------------------|---------------------------------------|
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Lamp Finish | Clear |
| Bulb shape | T29 29 mm |
| Approval and Application | |
| Energy Efficiency Class | G |
| Energy consumption kWh/1,000 hours | 40 KWh |
| EPREL registration number | 980883 |
| Product Data | |
| Full product code | 871951443255001 |
| Order product name | App 40.0W E14 230-240V T29 OV ICT/4x5 |
| EAN/UPC - product | 8719514432550 |
| Order code | 43255001 |
| Local order code | |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 20 |
| SAP material | 924103544402 |
| | |

Datasheet, 2021, November 22 data subject to change

Appliance Oven Tubular

| SAP net weight (piece) | 12.300 g |
|------------------------|--------------------------|
| ILCOS code | IBT/C-40-230/240-E14-29* |

Dimensional drawing

| Product | D (max) | C (max) |
|-----------------------------------|---------|---------|
| App 40.0W E14 230-240V T29 OV ICT | 29 mm | 58 mm |



APP 40.0W E14 230-240V T29 CL OV

