


Exeo D

672400.002 | Luminaires for escape route identification

Ceiling and wall luminaires
4051859437901
LED
L 255, B 48, H 177



self contained emergency luminaires for escape route identification
Housing: shockproof plastic (polycarbonate). Includes 4 legends and 1 white lay in plastic sheet for fitting in the transparent cover. Mounting bracket for wall mounting and two sealing screws included. Self-contained system with automatic self-test.

Emergency lighting

Emergency luminaire	Self-contained system
Battery Option	NiMH
Operating mode	Maintained power mode/Non-maintained power mode
Monitoring	Automatic self-test
Duration time	3 h
Viewing Distance	24 m

Colour

Colour	white
--------	-------

Dimensions

Length L	255 mm
Width B	48 mm
Height H	177 mm
Weight	750 g

Lamp

Lamp	LED
Colour temperature	4000K
Colour rendering index (CRI)	70
Photobiological safety according to EN 62471	Risk group 1

Electrical

Control gear	electronic
Voltage	220 - 240 V / 50 - 60 Hz

Approbations

Type of protection	IP 54
Protection class	II
Filament test	650°C - 30 seconds
Impact resistance	IK03 (0,35 Joule)
Safety marks	F-mark
Conformity mark	CE, EAC
Energieeffizienzklasse 2019/2015	C
Maintained power	=> 0 °C ... + 30 °C
Non-maintained power mode	=> 5 °C ... + 40 °C