



EXTRA1875CD

Supermarket Multideck Cooler

Product Features

- · Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3M1
- · Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory

Full Glass Door Multideck Cooler with Multiplexing Optio

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard. It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Measures and Content		
Total Display Area	m²	2.72
Temperature Range	°C	+2 to +6
Climate Class		3
Gross / Net Weight	kg	475 / 425
Gross / Net Volume	I	1350 / 1160
Design and Material		
Door No & Type		3 hinged glass doors
Tempered glass		Yes
Door Reversible		No
Shelves No & Type		4 black sheet, tilting + base
Shelf Color		Black
Max load on Shelves	kg/m²	100
Feet / Legs		6 adjustable feet
Castors		Option
Exterior Finish		Black / Glass
Interior Finish		Black
Interior Light		2 x Vertically LED
Lock		No
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	2x144
Thermometer		Yes
Power and Consumption		
Energy Class		C
Energy Consumption	kWh/24h	14.03
Annual Energy Cons.	kWh/year	5119
Input Power	W	1300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	53
Dimensions		
Internal Dimension (WxDxH)	mm	1875 x 610 x 1399
External Dimension (WxDxH)	mm	1975 x 920 x 2035
Packed Dimension (WxDxH)	mm	2075 x 975 x 2230
40ft Container Load	pcs	12





ilass end walls as standard

60x40 cm boxes fit perfectly