

COOL PRODUCTS WORLDWIDE



UR600X1

Storage Cooler GN2/1

Product Features


- · Stainless steel exterior
- Adjustable shelves GN2/1
- · Reversible solid door
- Integrated handle
- Fan assisted cooling
- Digital controller and temperature display
- · Adjustable feet with rollers to rear
- Lock

1-door storage cooler with GN2/1 shelves, stainless stee

The TEFCOLD UR is a classic storage cooler that combines time-tested reliability with a clean design, featuring a practical integrated handle. This particular model boasts an impressively low energy consumption, which is 57% lower than its predecessor. Ideal for demanding foodservice environments, this refrigerated cabinet comes with adjustable GN2/1 shelves with a remarkable load capacity of up to 25 kg per shelf. The storage fridge has fan-assisted cooling, and the temperature is easy to set on a digital thermostat. The UR range is available in various colors and sizes, and you can choose between solid door- or glass door models. See the UF range for freezer options.

Measures and Content		
Temperature Range	°C	-2 to +8
Climate Class		4
Gross / Net Weight	kg	107 / 100
Gross Volume	I	620
Gross / Net Volume	1	620 / 570
Design and Material		
Door No & Type		1 hinged solid door
Shelves No & Type		4 wire shelves white
Shelf Color		White
Shelf Dimensions		GN2/1
Max load on Shelves	kg/m²	196
Feet / Legs		2 adjustable feet
Castors		2 rollers
Exterior Finish		SS430
Interior Finish		White
Interior Light		No
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Fan assisted
Type of Defrost		Automatic-Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	70
Power and Consumption		
Energy Class		Α
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	0.79
Annual Energy Cons.	kWh/year	288
Power		13 Amp
Input Power	W	95
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45
Dimensions		
Internal Dimension (WxDxH)	mm	653 x 580 x 1660
External Dimension (WxDxH)	mm	777 x 745 x 1895
External Dimension (WxDxH) Packed Dimension (WxDxH)	mm mm	777 x 745 x 1895 840 x 765 x 2100







Strong castors as option