

Technical specifications

OVERALL DIMENSIONS 750x740x1260/1290 h

INTERNAL DIMENSIONS 610x410x760 h

POSITIVE CHILLING - PERFORMANCE +3° 25 kg

NEGATIVE CHILLING - PERFORMANCE -18° 20 kg

NUMBERS OF PANS (NOT INCLUDED) 10 - 1/1 GN 10 - 400x600

WEIGHT

kg 105

POWER W 1490

VOLTAGE 230 V/50 Hz

STRUCTURE stainless steel



ECO-FROST 10

ECO-FROST 5 can be used in different working sectors: restaurants, delicatessen, ice cream parlours. It has got an important internal capacity (5 trays), which allows you to blast chill different types of product in a short time. Thanks to its value for money it has a truly competitive market position.

Standard

BLAST CHILLING positive and negative

TRAY CADDY STRUCTURE for delicatessen and confectionery

DOOR GASKET pre heating

ROOM PROBE detects temperature inside the chamber

DRILL FOR TEMPERATURE in the heart of the product

TRAY FOR LIQUID POINTS during the defreezing activity

Options

- Gastronorm pans with different sizes
- Pastry pans with different sizes
- Voltage and special frequency





Capitale Sociale 100.000,00 € i.v. – Codice Fiscale, Partita Iva e nr. Iscr. Reg. Impr. PC n°01500110331 – R.E.A. 167804 - univacgroup.srl@pec.it VIA MAESTRI DEL LAVORO D'ITALIA, 24 - 29017 FIORENZUOLA D'ARDA (PC)

MACCHINE PER IL CONFEZIONAMENTO SOTTOVUOTO E INDUSTRIA ALIMENTARE IN GENERE (BREVETTI PROPRI)