



ECO-TYPE

Technical specifications

OVERALL DIMENSIONS

360x420x370 h

SIZE OF THE CHAMBER

260x300x120 h

SEALING BAR

mm 250

VACUUM PUMP

Q= 8 m³h-OIL

SEALING SYSTEM

impulse diaphragm

WEIGHT

kg 30

ABSORPTION

KW 0,75

VOLTAGE

230 V/50 Hz

STRUCTURE

stainless steel

ECO-TYPE is meant to be the entry level into the field of professional vacuum packaging chamber machines. Suitable for several sectors of employment, this model is easily recognizable for its top quality structure, its extremely high work capacity and also for its amazing and extremely advantageous price range

Standard

VAC STOP

forced interruption of the cycle

QUICK SEALING

forced anticipation of the sealing cycle

90° OPENABLE CARTER

helps the after sales maintenance

REMOVEABLE SEALING BAR

it facilitates to clean the chamber

CLEAN PUMP

oil is always clean inside the pump

GASTRO ATTACK

allows vacuum in containers

ROUNDED CHAMBER CORNERS

easier to clean the chamber

Options

- Inox trolley
- Inclined plane for liquids
- Voltage and special frequency
- Busch pump



Univac Group s.r.l. ■ Divisione



Capitale Sociale 100.000,00 € i.v. – Codice Fiscale, Partita Iva e nr. Iscr. Reg. Impr. PC n°01500110331 – R.E.A. 167804 - univacgroup.srl@pec.it

VIA MAESTRI DEL LAVORO D'ITALIA, 24 - 29017 FIORENZUOLA D'ARDA (PC)

MACCHINE PER IL CONFEZIONAMENTO SOTTOVUOTO E INDUSTRIA ALIMENTARE IN GENERE (BREVETTI PROPRI)