



FSC891H Black

Black 2-door display cooler with canopy

Product Features

- Approx. 58% more energy efficient than previous FSC-range
- LED illuminated canopy
- Internal vertical LED light
- Black interior and exterior
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors
- Adjustable feet with rollers to rear
- Digital temperature display

Black 2-door display cooler with canopy

The FSC range is with a an illuminated canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage. It has been updated and now uses in average 58% less energy compared to the previous models from the same range. This model is with black exterior and interior. The black exterior finish looks great, the black interior makes the content stand out - especially with LED lights perfectly illuminating the content. It is ideal for high-end cafes, delis and patisseries. It comes with 5 adjustable black wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Measures and Content		
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	166 / 153
Gross / Net Volume	I	707 / 535
Design and Material		
Door No & Type	2 hing	ed self-closing glass doors
Tempered glass		Ye
Door Reversible		No
Shelves No & Type		5 wire shelves white
Shelf Color		White
Shelf Dimensions		794 x 540 mm
Max load on Shelves	kg/m²	196
Canopy Type		D-Shape
Feet / Legs		4 adjustable fee
Castors		4 roller
Exterior Finish		Black RAL9005
Interior Finish		Black RAL9005
Interior Light		LE
Lock		Ye
Cooling and Functions		
Type of Controller		Electroni
Type of Cooling		Ventilated
Type of Defrost		Automati
Refrigerant		R29
Refrigerant Charge	g	11
Thermometer		Ye
Power and Consumption		
Energy Class		i i i i i i i i i i i i i i i i i i i
Energy Consumption	kWh/24h	2.63
Annual Energy Cons.	kWh/year	96
Input Power	W	41
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	4
Dimensions		
Internal Dimension (WxDxH)	mm	810 x 561 x 1556
External Dimension (WxDxH)	mm	890 x 740 x 1990
External Dimension (WxDxH) Packed Dimension (WxDxH)	mm mm	890 x 740 x 1990 950 x 840 x 2160





Illuminated canopy

Strong handles