

## ECO 35



**ECO 35** is for extremely demanding customers who look for high quality, solidity and working performances. It is characterized by high quality, long time granted reliability and total flexibility of the different models to operate in the most different sectors of use.

### Technical specifications

#### OVERALL DIMENSIONS

460x530x420 h

#### SIZE OF THE CHAMBER

360x400x190 h

#### SEALING BAR

mm 350

#### VACUUM PUMP

Q= 8/9.6 m<sup>3</sup>h-OIL

#### SEALING SYSTEM

impulse diaphragm

#### WEIGHT

kg 42

#### VOLTAGE

230 V/50-60 Hz

#### STRUCTURE

stainless steel

### Standard

#### VAC STOP

forced interruption of the cycle

#### QUICK SEALING

forced anticipation of the sealing cycle

#### 90° OPENABLE CARTER

helps the after sales maintenance

#### PROGRAM FOR MARINATING

meat and fish

#### DIGITAL CONTROL PANEL

9 programs

#### REMOVEABLE SEALING BAR

it facilitates to clean the chamber

#### CLEAN PUMP

oil is always clean inside the pump

#### GASTRO ATTACK

allows vacuum in containers

#### ROUNDED CHAMBER CORNERS

easier to clean the chamber

#### WORKING CYCLE COUNTER

with automatic maintenance alert

#### SOFT VAC

gradual re-entry of the air in chamber

### Options

- Inert gas injection
- Cableless piston sealing
- Inox trolley
- Inclined plane for liquids
- Voltage and special frequency
- Busch pump
- Lid hook



Univac Group s.r.l. ■ Divisione



Capitale Sociale 100.000,00 € i.v. – Codice Fiscale, Partita Iva e nr. Iscr. Reg. Impr. PC n°01500110331 – R.E.A. 167804 - univacgroup.srl@pec.it

VIA MAESTRI DEL LAVORO D'ITALIA, 24 - 29017 FIORENZUOLA D'ARDA (PC)

MACCHINE PER IL CONFEZIONAMENTO SOTTOVUOTO E INDUSTRIA ALIMENTARE IN GENERE (BREVETTI PROPRI)