



Measures and Content		
Internal Volume	m³	3.85
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Gross / Net Weight	kg	460 / 440
Gross / Net Volume	I	
Design and Material		
Door No & Type		1 hinged solid door
Max Load on Floor	kg/m²	2000
Exterior Finish		White
Interior Finish		White
Lock		Yes
Cooling and Functions		
		44363
Power and Consumption		
		44363
Dimensions		
Internal Dimension (WxDxH)	mm	1560 x 1260 x 1960
External Dimension (WxDxH)	mm	1800 x 1500 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1600 x 1300
40ft Container Load	pcs	14

CR 180x150x220

Coldroom Panels 120 mm

Product Features

- Only panels without cooling unit
- Interlocking connection system
- 120 mm panel insulation
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access

Cold room panels with 120 mm insulation

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. The interchangeable modular panels allow different positioning of the door, so you can build the room to fit your space. Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets. Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption. In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.



Strong handle

Lock system