



CR	240x	270x	220	WD
----	------	------	-----	----

Coldroom Panels 120 mm

Product Features

- 850 mm wide door
- Only panels without cooling unit
- Interlocking connection system
- 120 mm panel insulation
- Easy access to products
- Easy assembly
- Door position is fixed
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- · Ramp available as accessory for easy access

120 mm cold room panels with 850 mm wide door

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. This model has a 850 mm wide door, allowing easy access with a euro pallet. Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets. Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption. In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.

Measures and Content				
Internal Volume	m³	10.41		
Wall Thickness	mm	120		
Insulation Density	kg/m³	42		
Gross / Net Weight	kg	685 / 665		
Gross / Net Volume	T			
Design and Material				
Door No & Type		1 hinged solid door		
Max Load on Floor	kg/m²	2000		
Exterior Finish		White		
Interior Finish		White		
Lock		Yes		
Cooling and Functions				
	_	51055		
Power and Consumption				
		51055		
Dimensions				
Internal Dimension (WxDxH)	mm	2160 x 2460 x 1960		
External Dimension (WxDxH)	mm	2400 x 2700 x 2200		
Packed Dimension (WxDxH)	mm	2470 x 1860 x 1460		
40ft Container Load	pcs	4		





Strong handle

Lock system