



## **CRNF2121**

## Freezer room

## **Product Features**

- Plug-In ready after assembly
- Many customisation possibilities
- · Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Strip curtain included
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble. The cooling unit comes completely premounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door. The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks). Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system. Not suitable for outdoor use.

Measures and Content		
Internal Volume	m <sup>3</sup>	6.78
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	710 / 680
Gross / Net Volume	1	
Design and Material		
Door No & Type	1 hingeo	d solid door W:700 H:1765
Max Load on Floor	kg/m²	2000
Exterior Finish		White
Interior Finish		White
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes
Power and Consumption		
Max Ambient		40°C at 40% RH
Energy Consumption	kWh/24h	27.02
Annual Energy Cons.	kWh/year	9864
Power Supply		13 Amp
Input Power	W	1510
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60
Dimensions		
Internal Dimension (WxDxH)	mm	1860 x 1860 x 1960
External Dimension (WxDxH)	mm	2100 x 2100 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1900 x 2400
40ft Container Load	pcs	10





Strong handle

Shelf as accessory