



BLCA14X1

Blast Chiller/Freezer GN1/1

Product Features

- Touch screen controller
- Programmable thermostat
- HACCP compliant data export
- Guides for GN1/1 and Euronorm pans
- Stainless steel
- Core sensor included
- Reversible self-closing door
- Adjustable legs
- (Chill +70°C to +3°C) 55kg in 90 mins
- (Freeze +70°C to -18°C) 38kg in 240 mins
- Voltage / Frequency: 380-400/50 V/Hz

Blast chiller/freezer with touch screen controller

Our blast chiller/freezer range is perfect for quickly cooling or freezing hot food from the stove or oven, preserving the food in a safe way. The BLCA-X comes with an easy-to-use touch screen controller. Here you can choose one of the pre-set programs for different purposes or you can create and save your own programs. Primary programs are pre-set to keep the end temperature fixed until the cabinet is opened and the program is turned off. This method ensures the quality and safe preservation of the food and makes sure the food is safe for storage and later consumption. Cooling capacity is measured from +70 to +3 °C in 90 minutes - Freezing capacity for each model can be found under the technical specifications. The BLCA-X accepts both gastronorm 1/1 and euronorm pans (not included).

Measures and Content		
Capacity Cooling	kg	55
Capacity Freezing	kg	38
Capacity GN Pans	pcs	14
Temperature Range	°C	-18 to +70 / +3 to +70
Climate Class		4
Gross / Net Weight	kg	266 / 210
Gross / Net Volume	I	494 / 264
Design and Material		
Door No & Type		1 hinged self-closing solid door
Door Reversible		Yes
Feet / Legs		4 adjustable legs
Exterior Finish		SS304
Interior Finish		SS304
Interior Light		No
Lock		No
Cooling and Functions		
Type of Cooling		Blast
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	150
Power and Consumption		
Input Power	W	2000
Voltage / Frequency	V/Hz	380-400/50
Noise Level	dB(A)	60
Dimensions		
Internal Dimension (WxDxH)	mm	660 x 640 x 1170
External Dimension (WxDxH)	mm	800 x 815 x 2110
Packed Dimension (WxDxH)	mm	830 x 845 x 2125
40ft Container Load	pcs	26





Core sensor included

Touch screen controller