



CR 180x150x220

Cold Room Panels 80 mm

Product Features

- Only panels - without cooling unit
- Interlocking connection system
- 80 mm panel insulation
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access

Cold room panels with 80 mm insulation

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. The interchangeable modular panels allow different positioning of the door, so you can build the room to fit your space. Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets. Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption. In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.

Measures and Content

| | | |
|--------------------|-------------------|-----------|
| Internal Volume | m ³ | 4.48 |
| Wall Thickness | mm | 80 |
| Insulation Density | kg/m ³ | 42 |
| Gross / Net Weight | kg | 287 / 267 |
| Gross / Net Volume | l | |

Design and Material

| | | |
|-------------------|-------|---------------------|
| Door No & Type | | 1 hinged solid door |
| Max Load on Floor | kg/m² | 1500 |
| Exterior Finish | | White |
| Interior Finish | | White |
| Lock | | Yes |

Cooling and Functions

| | |
|--|-------|
| | 44360 |
|--|-------|

Power and Consumption

| | | |
|---------------------|----------|---|
| Energy Consumption | kWh/24h | 0 |
| Annual Energy Cons. | kWh/year | 0 |

Dimensions

| | | |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm | 1640 x 1340 x 2040 |
| External Dimension (WxDxH) | mm | 1800 x 1500 x 2200 |
| Packed Dimension (WxDxH) | mm | 2180 x 1280 x 1080 |
| 40ft Container Load | pcs | 16 |



Strong handle



Lock system