

22990001

Auxiliary contact position NO+NF SIRCO M 16-125A



General characteristics

- NO+NC auxiliary contacts: IP2 with front operation.

Access to resources (ex: manuals)

Pre-break and position 0 and I signalling by 1 NO/NC auxiliary contact or 2 NC auxiliary contacts.

Anticipate the switching of the main poles. They can be mounted on the left or on the right side of the device. Add up to 4 auxiliary contacts (2 modules).

Technical Characteristics

Weight [kg]	0.05
Number change-over contacts	2
Number NC contacts	1
Number NO contacts	1
Type	Auxiliary contact M type NO+NC

Classification

UNSPSC	39122233
ETIM Class	EC000041
IGCC	5290

Commerce

Effective date	2006-04-25
Offer Life Cycle Code	40
Country of origin	CN

ETIM - Electrical characteristics

Number of contacts as normally open contact	1
Number of contacts as normally closed contact	1
Rated operation current Ie at AC-15, 230 V [A]	6

ETIM - Mechanical characteristics

Type of electric connection	Screw connection
Mounting method	Side mounting

ETIM - Technical features

Lamp holder	None
-------------	------

Logistics

GTIN/EAN	3596031826407
Customs number	8536500700
Price unit	PC
Weight of the packing unit [kg]	0.05
Length of the packing unit [m]	0.085
Width of the packing unit [m]	0.07
Depth of the packing unit [m]	0.02