

26003119

Manual Load break switch SIRCO CD 3P 1250A 415 VAC Front Operation



Strong points

- Reliability and performance
- Safety of property and personnel
- Simplicity
- Easy to install

General characteristics

- Double positive break indication given through a position indication window, located directly on the product, and by the operating handle.
- Severe load duty categories (AC-22 and AC-23).
- High resistance to damp heat (supplied "tropicalised").

Compliance with standards

- IEC 60947-3

Access to resources (ex: manuals)

SIRCO are manually or remotely operated multipolar load break switches. They make and break under load conditions and provide safe isolation. SIRCO are designed for 415 VAC and DC low voltage electrical circuits.

Technical Characteristics

Length of the product unit [mm]	330
Width of the product unit [mm]	280
Depth of the product unit [mm]	140
Weight [kg]	10.35
Control operator	Direct : C2 / External : S4
Number of poles	3
Rated voltage	415 VAC / 500 VDC
Rated current [A]	1250
Type	Front Operation
Frame size	B6

Classification

UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290

Commerce

Description	Manually operated Load break switch SIRCO compact design frame B6 with 3 poles, 1250A, 415VAC/500VDC frontal direct operation with handle type C2 or frontal external operation with handle type S4. Delivered without handle
Effective date	2000-11-01
Offer Life Cycle Code	40
Country of origin	FR

Environmental Sustainability

PEP Filename	SOCO-00069-V01.01-EN.pdf
Climate change - Total - Cradle to Grave [kg CO ₂ eq.]	1198
Climate change - Total - Cradle to Gate [kg CO ₂ eq.]	62

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	500
Rated operating voltage [V]	400..500
Rated permanent current Iu [A]	1250
Rated permanent current at AC-23, 400 V [A]	1250
Rated permanent current at AC-21, 400 V [A]	1250
Rated short-time withstand current Icw [kA]	35
Rated operation power at AC-23, 400 V [kW]	750
Switching power at 400 V [kW]	750
Conditioned rated short-circuit current Iq [kA]	100
Number of poles	3

ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20

ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

Logistics

GTIN/EAN	3596031551729
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	10.35
Length of the packing unit [m]	0.22
Width of the packing unit [m]	0.4
Depth of the packing unit [m]	0.43

Norms

Conformity to standards	IEC
-------------------------	-----