



# SCHEMA TECNICA



| <b>STUDIO 54 Srl</b>                              | <b>SCHEMA TECNICA</b>                                    | <b>+32°C 60% UR</b> |                  |                  |
|---|--|---------------------|------------------|------------------|
| <b>DAIQUIRI 2001 BT ( GASTRONORM )</b>            |  | 2 Porte + motore    | 3 Porte + motore | 4 Porte + motore |
| <b>Codice prodotto</b><br><b>Item code no</b>     | <b>Produkt-Kode-Nr.</b><br><b>Nr. de code du produit</b> | <b>66104310</b>     | <b>66104490</b>  | <b>66104760</b>  |
|   |  |                     |                  |                  |
| External sizes in mm.                             |  | 1260x700x850        | 1720x700x850     | 2180x700x850     |
| Entrance hole sizes in mm.                        |  | 360x560x590         |                  |                  |
| Capacity ( Liters )                               |  | 300                 | 460              | 630              |
| Construction : External / Internal                |  | Acciaio Inox        |                  |                  |
| Feet<br>(Quantity – H min/max)                    |  | 4<br>145-210        | 4<br>145-210     | 5<br>145-210     |
| Door : - magnetic gasket<br>- Self closing.       |  | si<br>optional      |                  |                  |
| Insulation thickness scocca/porta (mm)            |  | 50 / 40             |                  |                  |
| Refrigeration                                     |  | ventilata           |                  |                  |
| Working temperature                               |  | -18-20° C           | -18-20° C        | -18-20° C        |
| Condenser fan ( W )                               |  | 10                  | 10               | 10               |
| Evaporator fan ( W )                              |  | 2x15                | 2x15             | 2x15             |
| Defrost   |  | elettronico         | elettronico      | elettronico      |
| Out-put ( W ) with ambient temp. +32° C           |  | 472W a -30°C        | 663W a -30°C     | 663W a -30°C     |
| Compressor  |  | E2134GK             | T2178GK          | T2178GK          |
| Compressor power ( Hp )                           |  | Hp 1/2              | Hp 1             | Hp1              |
| Refrigerating ( type and quantity )               |  | R404a 0.350 Kg      | R404a 0.350 Kg   | R404a 0.550 Kg   |
| Absorption ( W – A )                              |  | 537 – 3.4           | 840 – 4.1        | 840 – 4.1        |
| Voltage   |  | 230V/50Hz/1         |                  |                  |
| Lighting  |  | no                  |                  |                  |
| Control : - electronic device<br>- switch ON/OFF. |  | si<br>si            |                  |                  |
| Shelves ( Quantity )                              |  | 1 per vano          | 1 per vano       | 1 per vano       |
| Packaging sizes in mm.                            |  | 132x75x110          | 176x75x110       | 225x75x110       |
| netto/lordo weight in Kg.                         |  | 75/95               | 85/120           | 110/145          |

· Dati e caratteristiche soggetti a cambiamenti senza preavviso  
· All specification subject to change without notice

· Technische Daten und Eigenschaften mit Änderungen ohne Anzeige  
· Données techniques et caracteristiques sujettes à des changements sans avis